Filters, filter cartridges

Soler&Palau Ventilation Group

MFL - filter cartridge G4








- for circular piping
- includes a standard G4 filter (ISO coarse 60%)
- is made of galvanized steel with a rubber seal for connection to the pipe
- after releasing the locks on the lid, the frame with the filter can be removed
- MFR replacement filter cartridge
- · MFRR replacement filter insert including

∆p (Pa)	$\overline{}$							
150								
100							/	
50								
	_	_						
0	5	:	2 ;	3 4	1 :	5 6	3 7	7 m/s

Filter type	replacement filter	ØΑ	В	С	D	E
MFL 100	MFR 100	100	160	160	202	160
MFL 125	MFR 125	125	180	180	202	160
MFL 150/160	MFR 160	150/160	210	210	202	160
MFL 200	MFR 200	200	250	250	208	160
MFL 250	MFR 250	250	300	300	212	160
MFL 315	MFR 315	315	360	360	212	160
MFL 355	MFR 355	355	400	400	260	160
MFL 400	MFR 400	400	450	450	260	160
MFL 450	MFR 450	450	500	500	260	160
MFL 500	MFR 500	500	550	550	260	160

MFLU - insulated filter cartridge with carbon element







- · for circular piping
- contains a carbon filter including a G4 pre-filter (ISO coarse 60%)
- is made of galvanized steel with a rubber seal for connection to the pipe
- the filter cartridge is equipped with 10 mm thick Mirelon insulation
- · after releasing the locks on the lid, the frame with the filter can be removed
- MFRU replacement filter cartridge

∆ p (Pa)								
□ p (. α)								
150								
100								
100								
					_			
50				\sim				
	_							
0 ,								
0) 1	1 2	2 (3 4	4 5	5 6	3 7	m/s

Туре	Ø A [mm]	B [mm]	C [mm]	D [mm]	E [mm]
MFLU 125	125	200	199	196	154
MFLU 150	150	200	199	196	154
MFLU 160	160	200	199	196	154
MFLU 200	200	244	243	202	154