


KSE – vibration dampers

KSE-PAVZ



KSE-PAVZ are rubber vibration dampers for general use in air conditioning. It serves to isolate the transmission of low-frequency vibrations that are generated by fans and ventilation units.


- loading of the vibration damper is possible only in the direction of the axis of the fastening screw or beam
- optimized shape and material guarantee maximum attenuation of vibration transmission from the driver (fan) to the fixed mounting base
- vibration dampers can be used for all general applications in air conditioning and industry for mounting axial, radial and special fans, for mounting compressors, air conditioners, condensers, electric motors, etc.
- after installation, the period and method of checking the condition of the vibration dampers must be determined by the operating regulations, revisions must be carried out depending on the type of load and the environment

In case of uncertainty, contact our technical specialists, who will recommend a suitable silencer for each type of fan.

Type	A [mm]	B [mm]	C [mm]	D [mm]	Ø E [mm]	Ø F [mm]	max. load* [kg]
KSE-PAVZ-60 SH 45	60	90	24	76	M6	6.2	15
KSE-PAVZ-60 SH 60	60	90	24	76	M6	6.2	25
KSE-PAVZ-60 SH 75	60	90	24	76	M6	6.2	45
KSE-PAVZ-80 SH 45	80	120	27	100	M8	8.2	45
KSE-PAVZ-80 SH 60	80	120	27	100	M8	8.2	80
KSE-PAVZ-80 SH 75	80	120	27	100	M8	8.2	130
KSE-PAVZ-100 SH 45	100	148	28	124	M10	10.2	105
KSE-PAVZ-100 SH 60	100	148	28	124	M10	10.2	180
KSE-PAVZ-100 SH 75	100	148	28	124	M10	10.2	247
KSE-PAVZ-150 SH 45	150	214	39	182	M14	12.2	149
KSE-PAVZ-150 SH 60	150	214	39	182	M14	12.2	286
KSE-PAVZ-150 SH 75	150	214	39	182	M14	12.2	390

* for 1 silent-block

KSE



- rubber silent-block
- absorbs vibrations and reduces noise
- 1 package contains 4 pcs

Type	fan weight [kg]	A [mm]	B [mm]	C [mm]
KSE-45	40-100	25	30	M8
KSE-70	80-200	35	40	M8

71